

Vertical Intake Centrifugal Type Air Curtain (Plastic Type) 上吸风型离心式风幕机 (塑料型)



Ambient without heating 普通风

The integrated plastic casing gives a more streamlined appearance and stronger corrosion resistance performance.

Quality motor runs for 5000 hours continuously without any defects.

Multiple unit specifications: 900mm, 1200mm, 1500mm.

Various installation heights available: 3.0m, 3.5m, 4.0m, 4.5m.

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Height (m)	功率 Power (kW)	风速 Air Speed (m/s)	噪音 Noise (dB)	外形尺寸 Unit Size (mm)	净重 Net Weight (kg)	
FM3500L-2	900	220V~ / 50Hz / 1Ph	2.3-3.0	205	798	50	900 x 231.5 x 216	12.0	
FM3512L-2	1200			235	1064	51	1200 x 231.5 x 216	16.0	
FM3515L-2	1500			320	1330	52	1500 x 231.5 x 216	20.6	
FM3500L-2	900		3.0-3.5	3.0-4.0	295	1020	53	900 x 231.5 x 216	12.0
FM3512L-2	1200				360	1360	54	1200 x 231.5 x 216	16.0
FM3515L-2	1500				455	1700	55	1500 x 231.5 x 216	20.6
FM4000L-2	900		3.5-4.0	3.5-4.0	420	1388	58	900 x 231.5 x 216	12.0
FM4012L-2	1200				560	1864	59	1200 x 231.5 x 216	16.0
FM4015L-2	1500				710	2330	61	1500 x 231.5 x 216	20.6
FM4500L-2	900		4.0-4.5	4.0-4.5	475	1425	64	900 x 231.5 x 216	12.0
FM4512L-2	1200				625	1900	65	1200 x 231.5 x 216	16.0
FM4515L-2	1500				820	2375	66	1500 x 231.5 x 216	20.6

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。

Vertical Intake Centrifugal Type Air Curtain 上吸风型离心式风幕机



Ambient without heating 普通风

Metal casing, strong fire resistance, easy installation.

全金属外壳, 防火性能高, 安装方便。

Quality motor runs for 5000 hours continuously without any defects.

Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm & 1800mm.

Various installation heights available: 3.0m, 3.5m, 4.0m, 4.5m.

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Height (m)	功率 Power (kW)	风速 Air Speed (m/s)	噪音 Noise (dB)	外形尺寸 Unit Size (mm)	净重 Net Weight (kg)	
FM3005D	500	220V~ / 50Hz / 1Ph	2.3-3.0	155	532	49	605 x 230 x 212	9.9	
FM3010D	800			235	798	50	905 x 230 x 212	14.0	
FM3015D	1000			338	1064	51	1090 x 230 x 212	18.7	
FM3010D	800		3.0-3.5	3.0-4.0	308	1330	52	1450 x 230 x 212	27.0
FM3015D	1000				382	1650	52	1605 x 230 x 212	31.8
FM3020D	1200				422	1850	53	1805 x 230 x 212	36.6
FM3505D	500		3.0-3.5	3.0-4.0	211	1020	53	900 x 230 x 212	14.8
FM3510D	800				316	1270	53	1090 x 230 x 212	15.1
FM3515D	1000				422	1670	54	1260 x 230 x 212	18.7
FM3510D	800		3.5-4.0	3.5-4.0	527	1700	56	1500 x 230 x 212	23.6
FM3515D	1000				628	2040	57	1800 x 230 x 212	27.8
FM3520D	1200				733	2540	57	2000 x 230 x 212	31.9
FM4005D	500		3.5-4.0	3.5-4.0	284	1388	58	900 x 230 x 212	14.8
FM4010D	800				409	1864	58	1090 x 230 x 212	15.1
FM4015D	1000				508	2330	59	1290 x 230 x 212	18.7
FM4010D	800	4.0-4.5	4.0-4.5	663	1425	64	900 x 230 x 212	14.8	
FM4015D	1000			793	1900	65	1090 x 230 x 212	15.1	
FM4020D	1200			892	2375	66	1290 x 230 x 212	18.7	
FM4505D	500	4.0-4.5	4.0-4.5	283	950	63	800 x 230 x 212	9.9	
FM4510D	800			445	1425	64	900 x 230 x 212	14.8	
FM4515D	1000			566	1900	65	1090 x 230 x 212	15.1	
FM4510D	800	4.0-4.5	4.0-4.5	730	2375	66	1500 x 230 x 212	23.6	
FM4515D	1000			820	2850	68	1800 x 230 x 212	27.8	
FM4518D	1200			1050					

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。