


## Stainless Steel Cross-Flow Type Air Curtain 不锈钢贯流式风幕机



Ambient without heating 普通风



Stainless-steel casing, meeting different needs and easy cleaning. 全不锈钢外壳，适合于较多不同场所需要，环保且易于清洁。



The air wheel made of high-strength fiberglass plastic material, and the air wheel made of quality aluminum alloy, are especially suitable for the application of heavy oily smoke. 采用玻璃纤维材质的高强度塑料叶轮；另外还有优质铝合金结构叶轮，特别适用于油烟浓度大的地方使用。



Quality motor works for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。



Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm. 多种机身长度规格：900mm、1000mm、1200mm、1500mm。

### Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Height (m)	功率 Power(W)		风速 Air Speed (m/s)	风量 Air Flow (m³/h)	噪音 Noise (dB)	外形尺寸 Dimensions (mm)	净重 Net Weight (kg)
				低档Low	高档High					
FM3009-4-S	900	220V~50Hz/1Ph	2.3-3.0	189	195	11	1220	57	900×221×183	12.7
FM3010-4-S	1000			230	250		1450	55	1000×221×183	13.5
FM3012-4-S	1200			267	280		1710	59	1200×221×183	16.2
FM3015-4-S	1500			313	346		2230	60	1500×221×183	19.3
FM3009-Y-4-S	900			189	195		1220	57	900×221×183	12.7
FM3010-Y-4-S	1000			230	250		1450	55	1000×221×183	13.5
FM3012-Y-4-S	1200			267	280		1710	59	1200×221×183	16.2
FM3015-Y-4-S	1500			313	346		2230	60	1500×221×183	19.3

Remark: Customized rated voltage and frequency are available.

备注：可根据客户的额定电压和频率来做合适的产品。

## Powerful Air Volume Cross-Flow Type Air Curtain 大流量贯流式风幕机



Ambient without heating 普通风



Metal casing, Powerful air volume design. 全金属外壳，超大风量设计。



The air wheel, made of quality aluminum alloy, is especially suitable for the application of heavy oily smoke. 采用优质铝合金结构叶轮，特别适用于油烟浓度大的地方使用。



Quality motor works for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。



Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm. 多种机身长度规格：900mm、1000mm、1200mm、1500mm。

### Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Height (m)	功率 Power(W)		风速 Air Speed (m/s)		风量 Air Flow (m³/h)	噪音 Noise (dB)	外形尺寸 Dimensions (mm)	净重 Net Weight (kg)
				低档Low	高档High	低档Low	高档High				
FM1509-L-L	900	220V~50Hz/1Ph	3.0-3.5	280	350	12	2420	58	900×250×265	19.7	
FM1510-L-L	1000			300	380	15	2710	60	1000×250×265	20.6	
FM1512-L-L	1200			380	460		3400	63	1200×250×265	24.2	
FM1515-L-L	1500			420	560		4320	65	1500×250×265	27.8	

Remark: Customized rated voltage and frequency are available.

备注：可根据客户的额定电压和频率来做合适的产品。