

Water Heating Air Curtain 水热型风幕机



- Ambient without heating 普通风
- Hot water heating 水热型



Metal casing, strong fire resistance, simple installation and easy for maintenance.



The air wheel is made of aluminum, with good rigidity, corrosion resistance and long duration.



Heating by the hot water, energy consumption is saved and safer for users.



External rotor motor is using in this unit, which is smaller in size and lower in noise and longer duration. Reliable motor works for 5000 hours continuously with any defects.



The unit is inserted in the false ceiling that is invisible and matching perfectly with the exterior decoration.



The motor runs without failure for 5000 hours continuous.



Multiple length specifications available: 900mm, 1000mm, 1200mm, 1500mm, 1200mm & 1500mm.



Various installation heights are available: 3.5m, 4.0m, 4.5m.



Stainless steel or white powder-coating steel front panels are available.



The External Controller is easier for operation.

外置控制更简单易操作。

In-ceiling Type Air Curtain 天花板式风幕机



- Ambient without heating 普通风



The unit is inserted in the false ceiling that is invisible and matching perfectly with the exterior decoration.



The motor runs without failure for 5000 hours continuous.



Multiple length specifications available: 900mm, 1000mm, 1200mm, 1500mm, 1200mm & 1500mm.



Various installation heights are available: 3.5m, 4.0m, 4.5m.



Stainless steel or white powder-coating steel front panels are available.



The External Controller is easier for operation.

外置控制更简单易操作。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装 高度 Installation (m)	介质温度 Medium Temperature		散热 功率 Heat Power (KW)	电机 功率 Motor Power (W)	风量 Air Flow (m ³ /h)	风速 Air Speed (m/s)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
				进水 Inlet (°C)	出水口 Outlet (°C)							
RM-1210-WH-L	1000	220V~50Hz/1Ph	2.3~3.0	70	60	1343	150	1179	8	56	1000x350x217	20.3

Remark: Customized rated voltage and frequency are available. 备注: 可根据客户的额定电压和频率来订做合适的产品。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Installation (m)	功率 Power (W)	风速 Air Speed (m/s)	风量 Air Flow (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
FM3509C, FM3509GS	900			322		1020	53	900 × 340 × 230	17.2
FM3510C, FM3510GS	1000		3.0~3.5	322	14.3	1020	54	1000 × 340 × 230	18.5
FM3512C, FM3512GS	1200			419		1380	55	1200 × 340 × 230	20.9
FM3515C, FM3515GS	1500			536		1700	56	1500 × 340 × 230	28.0
FM4009C, FM4009GS	900			417		1398	58	900 × 340 × 230	17.2
FM4010C, FM4010GS	1000	220V~50Hz/1Ph	3.5~4.0	539	18.6	1398	59	1000 × 340 × 230	18.5
FM4012C, FM4012GS	1200			731		1864	61	1200 × 340 × 230	20.9
FM4015C, FM4015GS	1500			953		2330	63	1500 × 340 × 230	28.0
FM4509C, FM4509GS	900			553		1425	64	900 × 340 × 230	17.2
FM4510C, FM4510GS	1000		4.0~4.5	631	20.0	1425	65	1000 × 340 × 230	18.5
FM4512C, FM4512GS	1200			831		1900	66	1200 × 340 × 230	20.9
FM4515C, FM4515GS	1500			845		2375	68	1500 × 340 × 230	28.0

Remark: Customized rated voltage and frequency are available. 备注: 可根据客户的额定电压和频率来订做合适的产品。