





Pre-Positioned PTC Powerful Air Volume & Double Heating Air Curtain 前置PTC大风量双热量调节型热风幕机



 Ambient without heating
 PTC double heat settings 6 ~ 18kw PTC双温发热体功率6 ~ 18kw


 The high PTC heating power and powerful air volume design, can highly improve the heating performance and meet for higher installation height needs. It is suitable for regions with freezing climate, normally starting under 18°C environment.


 The high and low heating settings meets the demand of multiple applications and energy-saving.


 The un-electrified-surface PTC heater ensure safer operation, fast temperature rising and auto-temperature-control performance for users.


 Electronic control, either ambient air or heating air mode can be selected.


 Multiple unit specifications: 900mm、1000mm、1200mm、1500mm.

 The high PTC heating power and powerful air volume design, can highly improve the heating performance and meet for higher installation height needs. It is suitable for regions with freezing climate, normally starting under 18°C environment.

 The high and low heating settings meets the demand of multiple applications and energy-saving.

 The un-electrified-surface PTC heater ensure safer operation, fast temperature rising and auto-temperature-control performance for users.

 Electronic control, either ambient air or heating air mode can be selected.

 Multiple unit specifications: 900mm、1000mm、1200mm、1500mm.

Electrical Ratings 技术参数



产品型号 Model No.	规格 Specifications (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Installation (m)	出口温度 Outlet Temperature (°C)	风速 Air Speed (m/s)	发热体参数 PTC Heater Parameters				风量 Air Flow (m³/h)	噪音 Noise (dB)	外形尺寸 Unit Size (mm)	净重 Net Weight (kg)	
						低电压 功率 P _{Low} (W)	高电压 功率 P _{High} (W)	电阻 R _{Low} (Ω)	电阻 R _{High} (Ω)					
RM-1509-3D/K-1	900	380V ~ / 50Hz / 3PH	3.0 ~ 4.0	50 ~ 63	9 ~ 10	8000	12000	18	250	1512	62	900 x 285 x 265	22.4	
RM-1510-3D/K-1	1000					8000	12000	18	280	1695	62	1000 x 285 x 265	24.0	
RM-1512-3D/K-1	1200					7000	11	14000	20	300	2127	63	1200 x 285 x 265	27.5
RM-1515-3D/K-1	1500					9000	14	18000	28	320	2700	64	1500 x 285 x 265	31.5


Remark: Customized rated voltage and frequency are available.


备注: 可根据客户的额定电压和频率来订做合适的产品。


Post-Positioned PTC Powerful Air Volume & Double Heating Air Curtain 后置PTC大风量双热量调节型热风幕机



 Ambient without heating
 PTC double heat settings 6 ~ 14kw PTC双温发热体功率6 ~ 14kw


 The high PTC heating power and powerful air volume design, can highly improve the heating performance and meet for higher installation height needs. It is suitable for regions with freezing climate, normally starting under 18°C environment.

 The high and low heating settings meets the demand of multiple applications and energy-saving.


 The un-electrified-surface PTC heater ensure safer operation, fast temperature rising and auto-temperature-control performance for users.


 Electronic control, either ambient air or heating air mode can be selected.

 Multiple unit specifications: 900mm、1000mm、1200mm、1500mm.

 The high PTC heating power and powerful air volume design, can highly improve the heating performance and meet for higher installation height needs. It is suitable for regions with freezing climate, normally starting under 18°C environment.

 The high and low heating settings meets the demand of multiple applications and energy-saving.

 The un-electrified-surface PTC heater ensure safer operation, fast temperature rising and auto-temperature-control performance for users.

 Electronic control, either ambient air or heating air mode can be selected.

 Multiple unit specifications: 900mm、1000mm、1200mm、1500mm.

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specifications (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Installation (m)	出口温度 Outlet Temperature (°C)	风速 Air Speed (m/s)	发热体参数 PTC Heater Parameters				风量 Air Flow (m³/h)	噪音 Noise (dB)	外形尺寸 Unit Size (mm)	净重 Net Weight (kg)	
						低电压 功率 P _{Low} (W)	高电压 功率 P _{High} (W)	电阻 R _{Low} (Ω)	电阻 R _{High} (Ω)					
RM-1509-3D/K-2	900	380V ~ / 50Hz / 3PH	3.0 ~ 4.0	50 ~ 67	8 ~ 9	8000	9000	13.6	220	1231	58	900 x 280 x 265	22.0	
RM-1510-3D/K-2	1000					8000	9	9000	13.6	250	1368	59	1000 x 280 x 265	23.5
RM-1512-3D/K-2	1200					7000	11	11500	17.5	280	1641	60	1200 x 280 x 265	27.0
RM-1515-3D/K-2	1500					9000	14	14000	21.2	300	2052	62	1500 x 280 x 265	31.0

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。