

Cross-Flow Type Air Curtain For Freezer 冷库型贯流式风幕机



Ambient without heating 普通风

Metal casing, strong fire resistance, simple installation and easy cleaning. 全金属外壳，防火性能高，安装方便，容易清洗。

The air wheel made of high-strength fiberglass plastic material. 采用玻璃纤维材质的高强度塑料叶轮。

Quality motor works for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。

Multiple length specifications are available: 900mm, 1200mm, 1500mm. 多种机身规格供选择：900mm、1200mm、1500mm。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	功率 Power (W)	风速 Air Speed (m/s)	风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
LKFM3009	900	220V~/50Hz/1Ph	2.3~3.0	140	11.0	1450	55	900 × 183 × 183	10.0
LKFM3012	1200			185		57	1200 × 183 × 183	12.5	
LKFM3015	1500			225		58	1500 × 183 × 183	15.0	

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。

Powerful Air Volume Cross-Flow Type Air Curtain 大风量贯流式风幕机



Ambient without heating 普通风

Metal casing, Powerful air volume design. 全金属外壳，超大风量设计。

The air wheel, made of quality aluminum alloy, is especially suitable for the application of heavy oily smoke. 采用优质铝合金结构叶轮，特别适用于油烟浓度大的地方使用。

Quality motor works for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。

Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm. 多种机身长度规格：900mm、1000mm、1200mm、1500mm。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	功率 Power(W)		风速 Air Speed (m/s)		风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
				低档Low	高档High	低档Low	高档High				
FM1509-1-L FM1509-Y-1-L	900	220V~/50Hz/1Ph	3.0~3.5	280	350	12.0	15.0	2420	58	900 × 250 × 265	18.6
FM1510-1-L FM1510-Y-1-L	1000			300	380			2710	60	1000 × 250 × 265	19.5
FM1512-1-L FM1512-Y-1-L	1200			380	460			3400	63	1200 × 250 × 265	23.8
FM1515-1-L FM1515-Y-1-L	1500			420	560	4320	65	1500 × 250 × 265	27.8		
FM1610-1-L FM1610-Y-1-L	1000			245	355	3890	61	1000 × 250 × 265	19.6		
FM1612-1-L FM1612-Y-1-L	1200			320	440	4670	65	1200 × 250 × 265	24.2		
FM1615-1-L FM1615-Y-1-L	1500	420	540	5830	66	1500 × 250 × 265	27.9				

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。